

販売

玉掛けワイヤーロープ



販売

TSL型長シャックル



玉掛けワイヤーロープ安全荷重表(6×24)

ワイヤー ロープ径 (直径) (mm)	2本吊り(t)				4本吊り(t)			ロープ 破断荷重
	垂直	30°	60°	90°	30°	60°	90°	
6	0.60	0.57	0.51	0.42	1.14	1.02	0.84	1.81
8	1.07	1.01	0.91	0.75	2.03	1.82	1.50	3.22
9	1.35	1.28	1.15	0.94	2.57	2.30	1.89	4.07
10	1.67	1.59	1.42	1.17	3.18	2.84	2.34	5.03
12	2.40	2.28	2.04	1.68	4.56	4.08	3.36	7.24
14	3.28	3.11	2.78	2.29	6.23	5.57	4.59	9.85
16	4.30	4.08	3.65	3.01	8.17	7.31	6.02	12.9
18	5.42	5.14	4.60	3.79	10.2	9.21	7.58	16.3
20	6.70	6.36	5.69	4.69	12.7	11.3	9.38	20.1
22	8.10	7.69	6.88	5.67	15.3	13.7	11.3	24.3
24	9.66	9.17	8.21	6.76	18.3	16.4	13.5	29.0
26	11.3	10.7	9.62	7.92	21.5	19.2	15.8	34.0
28	13.1	12.4	11.1	9.18	24.9	22.3	18.3	39.4
30	15.0	14.3	12.8	10.5	28.6	25.6	21.0	45.2
32	17.1	16.3	14.5	12.0	32.6	29.1	24.0	51.5

TSL型長シャックル規格寸法

呼び 使用荷重 (Ton)	t (mm)	d (mm)	B (mm)	L1 (mm)	D (mm)	d1 (mm)	計算重量 (kg)	色あり
TSL-2.5t	16	16	45	130	38	16	0.85	オレンジ
TSL-4t	19	19	50	200	45	19	1.62	
TSL-6t	22	22	50	250	54	22	2.60	
TSL-8t	25	25	50	250	60	25	3.62	
TSL-14t	32	32	60	300	80	38	7.80	
TSL-20t	38	38	75	300	95	46	12.50	